



Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

1 Identification

· Product identifier

· Trade name: <u>551LSD</u>

· Article number: 551LSD

- · Relevant identified uses of the substance or mixture. Industrial Use Only.
- · Application of the substance / the mixture

Sealant Adhesive

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Dicor Products, an Airxcel brand

2965 Lavanture Place Elkhart, IN 46514

Information Phone Number: 574-264-2699

- · Information department: Global Regulatory Department.
- · Emergency telephone number:

ChemTrec: Day or Night within USA and Canada: 1-800-424-9300. Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

(Contd. of page 1)

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

6 % of the mixture consists of component(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1

3 Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture

(Contd. on page 3)

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

Contd. of page 2)

- Hazardous components:

64742-49-0 Naphtha (petroleum), hydrotreated light, low boil

13463-67-7 titanium dioxide

25-50%

2.5-10%

*

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

k

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

· Advice for firefighters

Firefighters use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

· Protective equipment: Protective clothing and respiratory protective device.

*

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

*

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Avoid contact with skin and eyes.

Open and handle receptacle with care.

(Contd. on page 4)

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

(Contd. of page 3)

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep container closed when not in use.

- · Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- · Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

13463-67-7 titanium dioxide

PEL Long-term value: 15* mg/m³

*total dust

REL See Pocket Guide App. A

TLV Long-term value: 10 mg/m³

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

· Eye protection:

Safety glasses with side shields.



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on	basic physical and	l chemical properties

· General Information

· Appearance:

Form: Paste Color: Light grey · Odor: Characteristic · Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Undetermined. Melting point:

Boiling point: 118-150 °C (244.4-302 °F)

14-18 °C (57.2-64.4 °F) · Flash point:

· Flammability (solid, gaseous): Not Applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

Product is not explosive. However, formation of explosive air/vapor · Danger of explosion:

mixtures are possible.

· Flammable limits:

Lower: Not Available Not Available Upper:

Not determined. · Vapor pressure:

1.17 · Specific gravity:

· Relative density Not determined. · Vapor density Not determined. · Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. Not determined. Kinematic:

· Solvent content:

Organic solvents: Not available

(Contd. on page 6)

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

(Contd. of page 5)

Solids content:	66.4 %	
· Other information	VOC: = 3.10 lb/gal OR 372 GRAMS/L Weight per gallon: = 9.23 LBS/gal	

10 Stability and reactivity

· Reactivity Not reactive as supplied

- · Chemical stability Stable under recommended storage conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Strong oxidizers, acids and bases.
- · Conditions to avoid Heat, flames, sparks.
- · Incompatible materials:

Reacts with oxidizing agents.

Reacts with acids.

Reacts with alkalis (bases)

· Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Skin irritant.
- · on the eye:

May irritate the eye.

Vapors may be irritating to the eyes.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

14807-96-6 Talc (Mg3H2(SiO3)4)	3
13463-67-7 titanium dioxide	2 <i>B</i>

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

(Contd. on page 7)

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

(Contd. of page 6)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Comply with current regulations.
- · Uncleaned packagings:
- · Recommendation: Comply with current regulations.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA
- · UN proper shipping name
- $\cdot DOT$
- · IMDG ADHESIVES (Naphtha), MARINE POLLUTANT

UN1133

Adhesives

- · IATA ADHESIVES
- · Transport hazard class(es)
- $\cdot DOT$





- · Class 3 Flammable liquids
- · Label
- · IMDG



- · Class 3 Flammable liquids
- · Label
- \cdot IATA



· Class 3 Flammable liquids

(Contd. on page 8)

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

	(Contd. of page
· Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances: Naphth
· Marine pollutant:	Yes (DOT)
-	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code).	: 33
EMS Number:	F- E , S - D
Stowage Category	B
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	Based on our review of the physical properties of this adhesive, Dicor Products has determined that this material can be reclassified as UN1133, Adhesives, 3, PGIII, when shipped in containers of less than 30 L (7.9 US GAL). The applicable statutes for this reclassification are 49 CFR § 173.121(b) for US ground shipments, IATA DG code § 3.3.3.1 for international air shipments, and IMDG code § 2.3.2.3 for international sea shipments.
· DOT	
· Remarks:	Special marking with the symbol (fish and tree).

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- \cdot Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

Please contact Dicor Products for more information regarding Proposition 65 on this product: 574-264-2699.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 9)

Printing Date 10/12/2021 Revision Number 4 Revision Date 06/28/2021

Trade name: 551LSD

 (Contd. of page 8)

 TLV (Threshold Limit Value)

 14807-96-6
 Talc (Mg3H2(SiO3)4)
 A4

 13463-67-7
 titanium dioxide
 A4

 • MAK (German Maximum Workplace Concentration)

 14807-96-6
 Talc (Mg3H2(SiO3)4)
 3B

 13463-67-7
 titanium dioxide
 3A

 • NIOSH-Ca (National Institute for Occupational Safety and Health)
 13463-67-7
 titanium dioxide

- · National regulations:
- · Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Dicor Products makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Dicor Products or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· Department issuing SDS:

Global Regulatory Department.

- · Creation Date: 06/28/2021
- · Contact:

Please contact Dicor Products for more information regarding Proposition 65 on this product: 574-264-2699.

- · Date of preparation / last revision 10/12/2021 / 3
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

...