

Elastomeric Roof Coating

SECTION 1

PRODUCT AND COMPANY INFORMATION

Product Name: Elastomeric Roof Coating 3
Version: Pigmented Acrylic Latex
Identifier 1: RP-CRC-1, RP-CRCT-1
Identifier 2: Mixture
Chemical Family: Elastomeric Roof Coating
Product Use:

Company Information: Dicor Products, an Airxcel brand
 2965 Lavanture Place
 Elkhart, IN 46514
 Phone: (574) 264-2699
 Internet Address: www.dicorproducts.com

24 Hour Emergency Contact: Chem Tel
 1-800-255-3924 (US & Canada)

SECTION 2

HAZARD(S) IDENTIFICATION

Pictogram(s):



Signal Word: WARNING

Hazard Statements:

H315	- Causes skin irritation.
H320	- Causes eye irritation.
H336	- May cause drowsiness or dizziness.

Precautionary Statements:

Prevention

P210	- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	- Avoid breathing dust/fumes/gas/mist/vapors/spray.
P264	- Wash skin thoroughly after handling.
P271	- Use only outdoors or in a well-ventilated area.
P280	- Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302+352	- IF ON SKIN: Wash with soap and water.
P304+P340	- IF INHALED: Move person to fresh air and keep comfortable for breathing.
P305+351+338	- IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses, if present, and easy to do. Continue rinsing.
P312	- Call a POISON CENTER or doctor/physician if you feel unwell.
P321	- Specific treatment (see additional information on this product's label)
P333 + P313	- If skin irritation occurs: Get medical advice/attention.
P337 + P313	- If eye irritation persists: Get medical advice/attention.
P362	- Take off contaminated clothing.
P363	- Wash contaminated clothing before reuse.

Storage

- P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.

Disposal

- P501 - Dispose of contents/container in accordance with federal, state, and local regulations.

SECTION 3**COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous Ingredients**

Chemical Name	CAS Number	Concentration (%)
Titanium Dioxide (Unbound)*	13463-67-7	0.00 - 10.00%
Calcium Carbonate (Unbound)*	1317-65-3	20.00 - 40.00%
Acrylic Polymer Emulsion	122055-81-6	20.00 - 40.00%
Water	7732-18-5	20.00 - 40.00%
Texanol	25265-77-4	0.0 - 10.00%
Formaldehyde	000050-00-0	> 1.00%
Propylene Glycol	57-55-6	> 2.00%
Cellulose, 2-hydroxyethyl ether	9004-62-0	> 1.00%
Diuron (ISO)	330-54-1	> 1.00%

*The hazards of the listed Titanium Dioxide and Calcium Carbonate are for their powder unbound forms. In the bound form and when used for application as a coating/texture for which the above product is designed, these ingredients are not hazardous.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4**FIRST-AID MEASURES**

- Eye Contact:** Immediately flush eye(s) with plenty of water, occasionally lifting the upper and lower eyelids and continue to rinse for at least 15-20 minutes. Remove contact lenses, if present, and easy to do so. Get medical attention if irritation persists.
- Inhalation:** Move to fresh air and seek medical attention if breathing is affected. Consult a physician after significant exposure, or feeling unwell.
- Skin Contact:** Wash off with soap and plenty of water after use. Contact a physician if rash or severe irritation develops.
- Ingestion:** Clean mouth with water and drink plenty of water afterwards. Do NOT induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recover position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt, or waistband.
- Most Important Symptoms and Effects, Both Acute and Delayed:** Irritant effects.
- Protection of First-Aiders:** No action shall be taken involving any personal risk or without suitable training. Use personal protective equipment as required (see Section 8). Show this Safety Data Sheet to the doctor in attendance.
- Notes to Physician:** Treat symptomatically.

SECTION 5

FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Use water, Carbon Dioxide, dry chemical, or foam as extinguishing media. Water based coating. Will not burn under normal circumstances.
Unsuitable Extinguishing Media:	N/A
Specific Extinguishing Methods:	Closed containers may explode when exposed to extreme heat. Water may be used to cool to prevent pressure build-up.
Special Protective Equipment for Fire-Fighters:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) pressure demand, MSHA/NIOSH (approved or equivalent).
Decomposition Products:	Thermal decomposition may produce toxic fumes of Carbon Monoxide, Carbon Dioxide, Sulfur Oxides, and Hydrogen.

SECTION 6

ACCIDENTAL RELEASE MEASURES

Handling Precautions:	Do not breathe dust/fume/gas/mist/vapors/spray. Use personal protective equipment as required. Deny access to unprotected persons. Use only outdoors or in a well-ventilated area.
Environmental precautions:	Do not flush into or allow chemical to enter into surface water or sanitary sewer system. If the product contaminates rivers, lakes, or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
Cleanup:	Soak up with vermiculite, floor absorbent, or other absorbent material (e.g. sand, silica gel, acid binder, or sawdust). Keep in suitable, closed containers for disposal.
Regulatory Requirements:	Follow applicable OSHA regulations (29 CFR 1940.120).

SECTION 7

HANDLING AND STORAGE

Handling Precautions:	Do not breathe dust/fume/gas/mist/vapors/spray. Avoid exceeding the given occupational exposure limits (see Section 8). Do not get in eyes, on skin, or on clothing. For personal protection, see Section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
Storage Requirements:	Store in original container and locked up. Keep container closed in a dry and well-ventilated place. Observe label precautions. Store locked up and in accordance with federal, state, and local regulations.

SECTION 8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Component	Basis	Value	Exposure Limit(s)* / Form of Exposure
Titanium Dioxide (Unbound)**	OSHA P1	TWA	15 mg/m ³ (Total Dust)
	ACGIH	TLV	10 mg/m ³ (Total Dust)
Calcium Carbonate (Unbound)**	OSHA	TWA	15 mg/m ³ (Total Dust)
	ACGIH	TLV	10 mg/m ³ (Total Dust)
Diuron (ISO)	OSHA	TWA	10 mg/m ³

	ACGIH	TLV	10 mg/m ³
Formaldehyde	OSHA	TWA	0.75 ppm
	ACGIH	TLV	NE

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**The hazards of the listed Titanium Dioxide and Calcium Carbonate are for their powder unbound forms. In the bound form and when used for application as a coating/texture for which the above product is designed, these ingredients are not hazardous.

Engineering Measures:

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal Protective Equipment:

Respiratory Protection

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye Protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove respiratory and skin/eye protection only after vapors have been cleared from the area. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid	Relative Density:	1.20
Color:	White	VOC:	78.6 g/L
Odor	Non-Descript	Vapor Pressure:	N/A
pH:	8.5 to 9.0	Volatile:	N/A
Flash Point:	Non-Flammable	Flammability Limit:	Non-Flammable
Melting Point:	N/A	Density:	N/A
Freezing Point:	N/A	Solubility:	100%
Boiling Point:	N/A	Viscosity:	N/A

SECTION 10

STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical Stability:	The product is chemically stable.
Possibility of Hazardous Reactions:	Stable under recommended storage conditions.
Conditions to Avoid:	Extremes of temperature and direct sunlight, as these conditions could lead to pressure build-up in a sealed container.

SECTION 11**TOXICOLOGICAL INFORMATION****Toxicity**

Hazardous Ingredient Name	Acute or Chronic?	Oral LD ₅₀	Dermal LD ₅₀	Dermal LC ₅₀
Propylene Glycol	No	20 mg/kg (rat)	20,800 mg/kg (rabbit)	N/A
Titanium Dioxide (Unbound)*	Chronic (Inhalation)	> 10,000 mg/kg (rat)	≥ 10,000 mg/kg (hamster)	N/A
Calcium Carbonate (Unbound)*	No	6,450 mg/kg (rat)	N/A	N/A
Polyphase 663 (Diuron)	No Inhalation	4958 mg/kg (rat) >2.05g/m ³ (rat)	>5000 mg/kg (rabbit)	N/A
Texanol	No	3,200 mg/kg (rat)	> 20 mL/kg (guinea pig)	N/A
Formaldehyde	Inhalation	1.8-4.0 mg/L (rat) 2974 mg/kg	>2000 mg/kg (rabbit)	N/A

*The hazards of the listed Titanium Dioxide and Calcium Carbonate are for their powder unbound forms. In the bound form and when used for application as a coating/texture for which the above product is designed, these ingredients are not hazardous.

Irritation:	Eye irritation Mild skin irritation
Sensitization:	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

SECTION 12**ECOLOGICAL INFORMATION**

Environmental Data	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by products should comply with the requirements of environmental protection and waste disposal legislation and any federal, state, and local requirements. This product contains material that can be hazardous to the environment.
Other Information:	Do not empty into drains; dispose of this material and its container in accordance with state and local regulations. Avoid dispersal of spilled material and runoff, and contact with soil, waterways, drains and sewers.

SECTION 13**DISPOSAL CONSIDERATIONS**

Disposal Methods:	<p>Waste from Residues Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any federal, state and local requirements.</p> <p>Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal in accordance with federal, state and local requirements.</p>
--------------------------	---

SECTION 14

TRANSPORT INFORMATION

Other Information: Non-regulated, not classified as dangerous.

SECTION 15

REGULATORY INFORMATION

TSCA List: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

CERCLA Reportable Quantity: This material does not contain any components with a CERCLA RQ.

SARA304 Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 302: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313:

	Product Name	CAS Number	%
Form R-Reporting requirements	Diuron (ISO)	330-54-1	15
	3-iodo-2-propynyl butyl carbamate	55406-53-6	3
Supplier Notification	Diuron (ISO)	330-54-1	15
	3-iodo-2-propynyl butyl carbamate	55406-53-6	3
	Formaldehyde	000050-00-0	5

Clean Air Act: This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65: **WARNING:** This product can expose you to chemicals including Titanium Dioxide and Formaldehyde which are known to the State of California to cause [cancer](#). For more information, go to www.P65Warnings.ca.gov.

WARNING: This product can expose you to chemicals including Diuron (ISO) which is known to the State of California to cause [birth defects or other reproductive harm](#). For more information, go to www.P65Warnings.ca.gov.

SECTION 16

OTHER INFORMATION

Previous Editions: First Edition: 03/21/2012
Revision Dates: 08/29/2018; 05/07/2021

Further Information: This SDS was prepared in accordance with OSHA regulatory standards for Toxic and Hazardous Substances: 29 CFR 1910.1200

Disclaimer: To the best of our knowledge, the information contained herein is accurate. However Dicor Products does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be handled with care. Although Dicor Products has described herein all of the hazards to which we are currently aware, we cannot guarantee that these are the only hazards which exist.